

ANNEX-C- PRICE PROPOSAL
LOT#1 MALGAGAI REFUGEE VILLAGE

A- REPAIR OF SCHOOL# 24

S.NO	DESCRIPTION	NO	UNIT	QUANTITY	RATE	TOTAL
1	Dismantling of two rooms 15x15 & 25x15 mud structure room completely with walls and take away the surplus material and dispose away 5 km from school.					
	dismantling of two rooms 15x15 & 25x15 mud structure room completely					
	Total		JOB	1.00		
2	Scraping old Mud Plaster Works Scraping the old / existing & damaged mud Plaster completely , any thickness including the cost of CARRIAGE OF Surplus Materials Includes Loading, Unloading .as per instruction					
	Total		CFT	2000.00		
3	Providing and laying 2mm thick plastic and layer of Mud Plaster 2 to 2.5 inch on roof of all schoolrooms and hall of school and toilets adding straw etc. As per instruction of engineer					
	Total covered area of roof		CFT	3000.00		
4	Construction of two toilets of size 6x6 with brick structure 9-inch wall, height 8 feet, roof with one girder and brick tile-T-iron, plaster from both sides, providing inside WC and pipe connection with one overhead tank of margin 300 Gallon, WC sewage connection with 20 feet deep digging of pit outside school 50 feet far .as per instruction of engineer					
	construction of toilets		JOBS	2.00		
5	Providing and laying Mud Plaster On Walls of rooms and hall of school including the cost of wood burada/straw					

	Mud Plaster NSR					
	Total		SFT	2000.00		
6	White washing three coats including dusting, filling the holes, cracks and removing inequalities using color and Gelo mixing in it at if any, at any height. Including cost of door paint as oil paint for 15 doors, roof Grider ,T-rion etc complete in all respect.					
	whitewash					
	Total		SFT	3000.00		
7	Distempering three coats including dusting, filling the holes, cracks and removing inequalities complete in all respect. As per instruction of engineer					
	Distempering					
	Total		SFT	2000.00		
8	Providing and fixing 5 mm glass panes of the following types in wooden or steel frames of doors, windows, ventilators etc complete in all respect including wooden gola beading in any floor, wooden notice board with frame. NSR- WINDOWS					
			SFT	150.00		
	TOTAL A- REPAIR OF SCHOOL# 24					

B- CONSTRUCTION OF BOUNDARY WALL SCHOOL# 24

S.NO	DESCRIPTION	NO	UNIT	QUANTITY	RATE	TOTAL
	CIVIL WORKS					
1	Dismantling of old mud brick wall and take away the surplus left material 5 km away from school					
		1	CFT	1600		
2	Excavation in foundation of buildings, bridges and other structures, depth up to 4 meters including dag bellings dressing, refilling around structures with excavated earth, watering and ramming lead up to 30 m lift to 1.5 m.					
		1	CFT	2000		
3	Providing and laying cement concrete thick and down 1:4:8 ratio using gauge in foundation including levelling compacting and curing. Extra if crushed stone 19mm (3/4") and down gauge is used in place of shingle or bajri					
		1	CFT	250		
4	Providing and laying 1:2:4 cement concrete using (3/4") thick and down gauge in foundation including levelling compacting and curing.					
		1	CFT	500		
5	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation, basement, and plinth.					

		1st step			
	2ND STEP				
		2nd			
			CFT	1312.50	
6	Providing and laying 4" (50mm) thick damp proof course with 1:2:4 cement concrete using Coarse Sand and crushed aggregate 1/2" (13mm) and down gauge mixed with any approved water proofing agent including compacting, curing, formwork, and its removal.				
	2" (50 mm) thick damp proof course.				
		1	CFT	562.50	
7	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in ground floor superstructure with ratio 1:4.				
		1			
	Deduction columns	50			
			CFT	2775.0	
8	Providing and laying cement concrete using crushed stone 19 mm (3/4") and down gauge in columns including compacting, curing, cost of form work and its removal in basement, and ground floor. Mix ratio is 1:2:4				
		1		487.50	
	COLUMN 03	7		39.375	
			CFT	526.875	
9	Providing and laying 1:2:4 cement concrete using approved coarse sand and crushed aggregate 3/4" (19mm) and down gauge in precast shelves coping , cornices, eave boards, hood, fencing posts and manhole covers etc. including formwork & its removal, compacting, and curing in ground floor.				
		1	CFT	140.63	
10	Pointing on brick work with cement sand mortar in plinth and ground floor including raking out joints and curing				
	(S.I No. 15-36 bii)	1			

			SFT	4000.00		
11	19 mm (3/4") thick cement plaster on walls and columns in basement, plinth and ground floor including making edges, corners, and curing. The mix ratio is 1:4 cement sand.					
		1	SFT	4000.00		
12	White washing three coats including dusting, filling the holes, cracks and removing inequalities, if any, at any height in any floor					
		2				
		50				
	TOTAL		SFT	8300.00		
28	Providing, fabricating, and laying deformed bars grade 40 having yield strength equal to 40,000 psi reinforcement for all kinds of R.C.C work in foundation, plinth, ground and first floor including the cost of straightening, removal of rust, cutting, bending, binding, wastage and providing such overlaps as are not shown on the drawings. The cost of binding wire and precast 1:2:4 cement concrete spacer blocks or M.S chair for binding and holding the reinforcement in position is inclusive.					
	Foundation					
	Columns					
	1/2" dia	4				
	Rings 3/8" dia	667.66667				
	pillar 1/2" dia	28				
	Rings 3/8" dia	667.66667				
	TOTAL		TON	1.611196688		
29	Providing and fixing barbed wire fencing comprising 1.5"x 1.5"x 3/16" angle iron post 3 ft long, 4 ft c/c embedded in cement concrete 1:4:8 base of 9"x 9"x 12" size with three rows of barbed wire 6" c/c including binding wire and painting of posts.					
	Barbed wire 3 ply, 12 gauge (2.17 mm) thick					

	TOTAL	1	RFT	500		
	TOTAL-B- CONSTRUCTION OF BOUNDARY WALL SCHOOL# 24					

C- CONSTRUCTION OF CLASS-ROOM 20 X 14 WITH VERANDAH SCHOOL NUMBER # 24

S.No	Description of Items	NO	UNIT	QUANTITY	RATE	TOTAL
	CIVIL WORKS					
	Excavation in foundation of buildings and bridges, including layout, dressing, refilling around structures with, excavated earth, watering & ramming lead up to 100 ft.,(30m) & lift up to 5 ft. (1.5m)					
	Excavation		CFT	296.00		
	Providing and laying plain hand mixed 1 : 4 : 8 cement concrete using sand approved source and crushed aggregate having maximum size up to 1-1/2" (38mm) & down gauge in foundation and plinth including leveling, compacting & curing.					
	Lean		CFT	37.00		
	Providing, fabricating, and laying deformed Grade 60 steel reinforcement (deformed bar) for all kinds of R.C.C work in foundation, plinth and ground floor including the cost of straightening, removal of rust, cutting, bending, binding, wastage and providing such over-laps as are not shown on the drawings. The cost of binding wire and cement concrete spacer blocks or chairs for binding and holding the reinforcement in position is inclusive up to 15 ft. (5m) height					
	Steel					
	Foundation and Columns			1.16		

	Plinth Band			0.48		
	Door Band			0.39		
	Roof Beam			0.38		
	Slab			1.11		
	Total		TON	3.520		
	Providing and laying 1:2:4 cement concrete using approved coarse sand and crushed aggregate 3/4" (19mm) and down gauge in sills and Bed Plate including formwork and its removal, compacting and curing					
	Foundation beam and footing		CFT	139.50		
	Providing and laying first class solid burnt brick masonry (Brick Strength:1800psi-2000psi) including scaffolding, raking out joints and curing in ground floor superstructure and i/c cost of testing with 1:3					
	Foundation bricks		CFT	214.08		
	Providing and laying 1 : 2 : 4 cement concrete using approved coarse sand and crushed aggregate 3/4" (19mm) & down gauge in foundation including leveling, compacting, and curing.					
	Column		CFT	81.00		
	Providing and laying 1:2:4 cement concrete using approved coarse sand and crushed aggregate 3/4" (19mm.) and down gauge in plinth band , door band and roof band of required shape or section including formwork and its removal, compacting, and curing in basement and ground floor but excluding the cost of reinforcement.					
	Plinth beam		CFT	122.63		

	Providing and laying first class solid burnt brick masonry (Brick Strength:1800psi-2000psi) including scaffolding, raking out joints and curing in ground floor superstructure and i/c cost of testing with 1:3					
	Brick		CFT	427.56		
	Providing and laying 1:2:4 cement concrete using approved coarse sand and crushed aggregate 3/4" (19mm.) and down gauge in plinth band, door band and roof band of required shape or section including formwork and its removal, compacting, and curing in basement and ground floor but excluding the cost of reinforcement.					
	Door band		CFT	81.28		
	Filling and compacting soil, earth, and boulders behind retaining walls (including excavation of soil and lead up to 50 ft. (15m)					
	Filling		CFT	432.00		
	Providing and laying plain hand mixed 1 : 4 : 8 cement concrete using sand approved source and crushed aggregate having maximum size up to 1-1/2" (38mm) & down gauge in foundation and plinth including leveling, compacting & curing.					
			CFT	144.00		
	Cement plaster using Coarse Sand on soffits of ceiling, cantilever slabs, sides, and soffits of beams, in basement and ground floor including making edges, corners and curing. 1/2 inch (13mm) thick cement sand plaster 1:4					
	Ceiling Plaster		SFT	480.00		
	3/4 inch (19mm) thick cement plaster using Coarse Sand on walls and columns in basement, plinth and ground floor including making edges, corners, and curing. The mix ratio is 1:4 cement sand.					
	Inside Plaster		SFT	968.00		

	Providing and laying 1:2:4 cement concrete using approved coarse sand and crushed aggregate 3/4" (19mm) and down gauge in slabs including formwork and its removal, compacting, and curing Up to 6" (150 mm) thickness i) In basement, plinth, and ground floor					
	Flooring		CFT	158.40		
	Providing and laying Conglomerate flooring (two coat work) having 1/2" (9mm) thick wearing surface comprising 1 part of cement & 2 parts of stone chips passing 3/16" sieve, over 1:3:6 concrete base using crushed aggregate laid in panels or approved pattern including formwork, curing, and surface finishing as approved by Engineer In charge. mortar.					
	Plinth protection		CFT	55.00		
	Providing and fixing moulded steel door frame of approved profile, manufactured from zinc-coated mild steel sheets 16 gauge made by Shahah Industries or equivalent standard conforming to B.S.S.1245, treated with special primer base paint all round, fitted with six fixing lugs, three steel hinges for fixing door shutters standard lock-strike plate, one sliding holt eye, and three rubber buffers, including cutting holes and making good damages to walls and filling the door frame cavity with lean cement mortar 1:4 as directed by the Engineer					
	Front door and window frame		RFT	20.00		
	Providing and fixing 3" thick First class approved wood (Keil) shutter fixed with wooden sheet and with approved nickle plated hinges and tower bolts Handle and handle Locks					
	Door		Sft	32.00		
	Providing and fixing fully glazed single leaf hung/sliding aluminium windows, ventilators (Deluxe model - 2mm) of anodized champagne or approved colour of Prime, Chawala, Pakistan Cable or any approved					

	section as approved by Engineer in charge including aluminium fittings, 5 mm local tinted glass, lugs, cutting holes and making good the damages to walls.					
	Windows		SFT	126.00		
	Providing and fixing windows steel grill of 12mm x 12 mm filled 18 gauge with wire mesh on it fixed in wall cement in proper way not exposed to external wall of any approved section as approved by Engineer in charge including fittings, making good two coat of red oxide and two coat of oil paint without the damages to walls.					
	windows grill with wire mesh		SFT	126.00		
	Applying matt finish including cost of coat premier and wall Patti and with approved brand (Berger, ici or equivalent) synthetic polyvinyl emulsion finish of approved shade in two or more coats over and including the cost of priming coat including preparation of surface viz. dusting, sand papering or rubbing with pumice stone, filling cracks or holes, if any, removing blisters or other imperfections at any height and any floor. (@ at least 2.20 litre per 10 sq.m) as per approved colour and design					
	Matt finish Paint inside		SFT	480.00		
	Applying weather resistant paint coating such as ICI weather shield, Berger weather coat or equivalent to interior or exterior walls or ceiling including supplying all labour, materials, scaffoldings, and removal of debris etc. @ at least 3.50 litre per 10 as per approved colour and design					
	Weather coats outside		SFT	714.00		

	<p>Painting in ground floor or basement with Robbialac or equivalent super gloss synthetic enamel paint in two or more coats as per manufacturer's instruction on woodwork over and including the cost of priming coat, surface preparation, rubbing down smooth, knotted, filling cracks, holes, and joints.</p>					
	<p>Door paint and Black board</p>		SFT	50.00		
	<p>ELECTRIC WORK OF BUILDING</p>					
	<p>Providing and installing 6 Nos of 25w Led Lights, 2 Nos of 56" DC Fan with each one attached to Solar Plate of 150w (with proper frame installed on roof) with proper wiring in slab ceiling connection with lights and fans and 8 gange switches with automatic solar control regularator for fan , installation complete in all respect.</p>					
			JOB	1.00		
<p>C- CONSTRUCTION OF CLASS-ROOM 20 X 14 WITH VERANDAH SCHOOL NUMBER # 24</p>						

D- REPAIR OF MUD STRUCTURE SCHOOL# 25

S.NO	DESCRIPTION	NO	UNIT	QUANTITY	RATE	TOTAL
1	Scraping old Mud Plaster Works Scraping the old / existing & damaged mud Plaster completely , any thickness including the cost of CARRIAGE OF Surplus Materials Includes Loading, Unloading .as per instruction					
	Total		CFT	3000.00		
2	Dismantling of three mud structure toilets 6 x6 and filling the Pits with same materail, 100 feet mud structure boundary wall as per instruction mud structure toilet and boundary wall dismantling					
	Total		SFT	1.00		
3	Construction of three toilets of size 6x6 with brick structure 9-inch wall, height 8 feet, roof with one girder and brick tile-T-iron, plaster from both sides, providing inside WC and pipe connection with one overhead tank of marjan 300 Gallon , WC sewage connection with 20 feet deep digging of pit outside school 50 feet far .as per instruction of engineer					
	construction of toilets		JOBS	3.00		

	Providing and laying 2mm thick plastic and layer of Mud Plaster 2 to 2.5 inch on roof of all schoolrooms and hall of school and toilets adding straw etc. As per instruction of engineer					
	Total covered area of roof		CFT	3000.00		
	Providing and laying Mud Plaster On Walls of school including the cost of wood burada/straw					
	Mud Plaster NSR					
	Total		SFT	5000.00		
	White washing three coats including dusting, filling the holes, cracks and removing inequalities using colour and Gelo mixing in it at if any, at any height. Including cost of door paint as oil paint for 22 doors, roof Grider ,T-rion etc complete in all respect. Whitewash					
	Total		SFT	5000.00		
	Distempering three coats including dusting, filling the holes, cracks and removing inequalities complete in all respect. As per instruction of engineer					

	Total		SFT	2000.00		
	Providing and fixing 5 mm glass panes of the following types in wooden or steel frames of doors, windows, ventilators etc complete in all respect including wooden gola beading in any floor, wooden notice board with frame.		SFT			
	TOTAL OF D- REPAIR OF MUD STRUCTURE SCHOOL# 25					
TOTAL- D- REPAIR OF MUD STRUCTURE SCHOOL# 25						

E- CONSTRUCTION OF BOUNDRY WALL SCHOOL# 25

S.NO	DESCRIPTION	NO	UNIT	QUANTITY	RATE	TOTAL
	CIVIL WORKS					
	dismantling of old mud brick wall and take away the surplus left material 5 km away from school					
		1	CFT	4000		
	Excavation in foundation of buildings, bridges and other structures, depth up to 4 meters including dag bellings dressing, refilling around structures with excavated earth, watering and ramming lead up to 30 m lift up to 1.5 m.					
		1	CFT	2000		

	Providing and laying cement concrete thick and down 1:4:8 ratio using gauge in foundation including levelling compacting and curing. Extra if crushed stone 19mm (3/4") and down gauge is used in place of shingle or bajri					
		1	CFT	250		
	Providing and laying 1:2:4 cement concrete using(3/4") thick and down gauge in foundation including levelling compacting and curing.					
		1	CFT	500		
	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation, basement, and plinth.					
		1st step				
	2ND STEP					
		2nd				
			CFT	1312.50		
	Providing and laying 4" (50mm) thick damp proof course with 1:2:4cement concrete using Coarse Sand and crushed aggregate 1/2" (13mm) and down gauge mixed with any approved water proofing agent including compacting, curing, formwork, and its removal. 2" (50 mm) thick damp proof course.					
		1	SFT	562.50		
	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in ground floor superstructure with ratio 1:4.					
		1				
	Deduction columns	50				
			CFT	2775.0		
	Providing and laying cement concrete using crushed stone 19 mm (3/4") and down gauge in columns including compacting, curing, cost of form work and its removal in basement, and ground floor. Mix ratio is 1:2:4					
		1		68.25		

	COLUMN 03	50		281.25		
			CFT	349.5		
	Providing and laying 1:2:4 cement concrete using approved coarse sand and crushed aggregate 3/4" (19mm) and down gauge in precast shelves coping , cornices, eave boards, hood, fencing posts and manhole covers etc. including formwork & its removal, compacting, and curing in ground floor.					
		1				
			CFT	140.63		
	Pointing on brick work with cement sand mortar in plinth and ground floor including raking out joints and curing					
	Pointing on brick work with cement sand mortar in plinth and ground floor including raking out joints and curing					
	(S.I No. 15-36 bii)	1				
			SFT	4000.00		
	19 mm (3/4") thick cement plaster on walls and columns in basement, plinth and ground floor including making edges, corners, and curing. The mix ratio is 1:4 cement sand.					
		1				
			SFT	4000.00		
	White washing three coats including dusting, filling the holes, cracks and removing inequalities, if any, at any height in any floor					
		2				
		50				
			SFT	8234.38		
	Providing, fabricating, and laying deformed bars grade 40 having yield strength equal to 40,000 psi reinforcement for all kinds of R.C.C work in foundation, plinth, ground and first floor including the cost of straightening, removal of rust, cutting, bending, binding, wastage and providing such overlaps as are not shown on the drawings. The cost of					

	binding wire and precast 1:2:4 cement concrete spacer blocks or M.S chair for binding and holding the reinforcement in position is inclusive.					
	Foundation					
	Columns					
	1/2" dia	4				
	Rings 3/8" dia	667.66667				
	pillar 1/2" dia	28				
	Rings 3/8" dia	667.66667				
				Ton	1.071139509	
	Providing and fixing barbed wire fencing comprising 1.5"x 1.5"x 3/16" angle iron post 3 ft long, 4 ft c/c embedded in cement concrete 1:4:8base of 9"x 9"x 12" size with three rows of barbed wire 6" c/c including binding wire and painting of posts.					
		1		RFT	500	
TOTAL- E- CONSTRUCTION OF BOUNDRY WALL SCHOOL# 25						

F- REPAIR WORK OF SCHOOLSCHOOL# 26

S.NO	DESCRIPTION	NO	UNIT	QUANTITY	RATE	TOTAL
1	Scraping old Mud Plaster Works Scraping the old / existing & damaged mud Plaster completely , any thickness including the cost of CARRIAGE OF Surplus Materials Includes Loading, Unloading .as per instruction					
	Total		CFT	5000.00		
2	Providing and laying 2mm thick plastic and layer of Mud Plaster 2 to 2.5 inch on roof of all schoolrooms and hall of school and toilets adding straw etc. As per instruction of engineer					
	Total covered area of roof		CFT	5000.00		
3	Providing and laying Mud Plaster on Walls of rooms and hall of school including the cost of wood burada/straw Mud Plaster NSR					
	Total		SFT	10180.00		
4	White washing three coats including dusting, filling the holes, cracks and removing inequalities using colour and Gelo mixing in it at if any, at any height. Including cost of door paint as oil paint for 22 doors, roof Grider ,T-rion etc complete in all respect. whitewash					

	Total		SFT	8000.00		
5	Distemping three coats including dusting, filling the holes, cracks and removing inequalities complete in all respect. As per instruction of engineer Distemping					
	Total		SFT	2000.00		
6	Providing and fixing 5 mm glass panes of the following types in wooden or steel frames of doors, windows, ventilators etc complete in all respect including wooden gola beading in any floor, wooden notice board with frame.		SFT	312.00		
TOTAL- F- REPAIR WORK OF SCHOOLSCHOOL# 26						

G- CONTRUCTION OF BOUNDRY WALL OF SCHOOLSCHOOL# 26

S.NO	DESCRIPTION	NO	UNIT	QUANTITY	RATE	TOTAL
	CIVIL WORKS					
	dismantling of old mud brick wall and take away the surplus left material 5 km away from school					
		1	CFT	560		
	Excavation in foundation of buildings, bridges and other structures, depth upt 4 meters including dag bellings dressing, refilling around structures with excavated earth, watering and ramming lead up to 30 m lift up to 1.5 m.					
		1	CFT	280		

	Providing and laying cement concrete thick and down 1:4:8 ratio using gauge in foundation including levelling compacting and curing. Extra if crushed stone 19mm (3/4") and down gauge is used in place of shingle or bajri					
		1	CFT	35		
	Providing and laying 1:2:4 cement concrete using(3/4") thick and down gauge in foundation including levelling compacting and curing.					
		1	CFT	70		
	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation, basement, and plinth.					
		1st step				
	2ND STEP					
		2nd				
			CFT	183.75		
	Providing and laying 4" (50mm) thick damp proof course with 1:2:4cement concrete using Coarse Sand and crushed aggregate 1/2" (13mm) and down gauge mixed with any approved water proofing agent including compacting, curing, formwork, and its removal .					
	2" (50 mm) thick damp proof course.					
		1	SFT	78.75		
	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in ground floor superstructure with ratio 1:4.					
		1				
	Deduction columns	7				
			CFT	388.5		
	Providing and laying cement concrete using crushed stone 19 mm (3/4") and down gauge in columns including compacting, curing, cost of form work and its removal in basement, and ground floor. Mix ratio is 1:2:4					
		1		68.25		
	COLUMN 03	7		39.375		
			CFT	107.625		

	Providing and laying 1:2:4 cement concrete using approved coarse sand and crushed aggregate 3/4" (19mm) and down gauge in precast shelves coping , cornices, eave boards, hood, fencing posts and manhole covers etc. including formwork & its removal, compacting, and curing in ground floor.					
		1				
			CFT	19.69		
	Pointing on brick work with cement sand mortar in plinth and ground floor including raking out joints and curing					
	(S.I No. 15-36 bii)	1				
			SFT	560.00		
	19 mm (3/4") thick cement plaster on walls and columns in basement, plinth and ground floor including making edges, corners, and curing. The mix ratio is 1:4 cement sand.					
		1				
			SFT	560.00		
	White washing three coats including dusting, filling the holes, cracks and removing inequalities, if any, at any height in any floor					
		2				
		7				
			SFT	1136.41		
	Providing, fabricating, and laying deformed bars grade 40 having yield strength equal to 40,000 psi reinforcement for all kinds of R.C.C work in foundation, plinth, ground and first floor including the cost of straightening, removal of rust, cutting, bending, binding, wastage and providing such overlaps as are not shown on the drawings. The cost of binding wire and precast 1:2:4 cement concrete spacer blocks or M.S chair for binding and holding the reinforcement in position is inclusive.					
	Foundation					
	Columns					

	1/2" dia	4				
	Rings 3/8" dia	94.333333				
	pillar 1/2" dia	28				
	Rings 3/8" dia	94.333333				
				Ton	0.222273438	
	Providing and fixing barbed wire fencing comprising 1.5"x 1.5"x 3/16" angle iron post 3 ft long, 4 ft c/c embedded in cement concrete 1:4:8 base of 9"x 9"x 12" size with three rows of barbed wire 6" c/c including binding wire and painting of posts.					
	Barbed wire 3 ply, 12 gauge (2.17 mm) thick					
		1		RFT	70	
TOTAL- G- CONTRUCTION OF BOUNDRY WALL OF SCHOOLSCHOOL# 26						

H- REPAIR OF SCHOOL# 27

S.NO	DESCRIPTION	NO	UNIT	QUANTITY	RATE	TOTAL
1	Scraping old Mud Plaster Works Scraping the old / existing & damaged mud Plaster completely , any thickness including the cost of CARRIAGE OF Surplus Materials Includes Loading, Unloading .as per instruction					
	Total		CFT	3000.00		

2	Providing and laying 2mm thick plastic and layer of Mud Plaster 2 to 2.5 inch on roof of all schoolrooms and hall of school and toilets adding straw etc. As per instruction of engineer					
	Total covered area of roof		CFT	3000.00		
	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in ground floor superstructure with ratio 1:4.					
	Bricks work before replacing roof	1.0	CFT	172.80		
3	Dismantling roof of store size 22x14' and replacing with new by providing 8x6 girder at 4 feet distance ,T-iron at horizontal at spacing of 2 feet and roof covering material available locally of 2mm plastic,straw,keerd and mat as per instruction.					
	Roof replacement					
	Total		SFT	375.00		
3	White washing three coats including dusting, filling the holes, cracks and removing inequalities using colour and Gelo mixing in it at if any, at any height. Including cost of door paint as oil paint for 22 doors, roof Grider ,T-rion etc complete in all respect. whitewash					
				5000.00		

				4100.00		
	Total		SFT	9100.00		
3	Distempering three coats including dusting, filling the holes, cracks and removing inequalities complete in all respect. As per instruction of engineer					
	Distempering					
	Total		SFT	4000.00		
4	Providing and fixing 5 mm glass panes of the following types in wooden or steel frames of doors, windows, ventilators etc complete in all respect Including wooden gola beading in any floor, wooden notice board with frame. WINDOWS		SFT	150.00		
TOTAL-H- REPAIR OF SCHOOL# 27						
TOTAL (A+B+C+D+E+F+G+H)						

Name of Company: _____

Name of Bidder: _____

Company Stamp:

Signature:

Date:
